

IDENTIFICATION

OUTDOOR MORPHOACCESS®

500 SERIES

FINGERPRINT IDENTIFICATION TERMINAL

DESIGNED FOR OUTDOOR ACCESS CONTROL



IP 65 weatherproof

Fast, accurate and reliable

Multifactor authentication

Up to 50,000 users in one-to-many identification mode

Easy integration into existing systems

Power-Over-Ethernet (POE)

Integrated MIFARE® and DESFire® reader/encoder

OUTDOOR MORPHOACCESS® 500 SERIES

FINGERPRINT IDENTIFICATION TERMINAL

DESIGNED FOR OUTDOOR ACCESS CONTROL



The Outdoor MorphoAccess® 500 Series (OMA 500) are versatile biometric terminals intended for access control and time & attendance. They use Morpho's proprietary algorithms, which have acquired worldwide reputation for their accuracy and levels of performance. Fast and network capable, they can address all security applications, from one-door control to the protection of buildings, warehouses, vast infrastructures and government agencies.

They offer value-added retailers and access control manufacturers a reliable, powerful and scalable solution.

The know-how of the world N°1

- **Wide-area, accurate fingerprint sensor**, FBI PIV IQS certified, capable of withstanding harsh climatic environments
- The OMA 500 terminals offer the **highest level of security** on the market
- **Fast**: 0.7 sec in authentication mode and 0.9 sec in 1:1000 identification mode (including detection, coding and matching)
- **Accurate**: depending on the required level of security, the false acceptance rate (FAR) can be configured down to 10^{-8}

Powerful capabilities in a small package

- **IP 65 rated** terminal mounted in a hardened, weatherized housing
- The **highest database capacity** on the market: up to 100,000 fingerprint templates stored, with license
- **Multifactor authentication**: with MIFARE® and DESFire® ISO 14443-A & B smartcard reader/encoder, fingerprint and PIN code
- Operates in **standalone** or **networked** modes. For small populations, it is possible to capture fingerprints and encode badges on the terminal itself.
- Equipped with numerous interfaces for **easy integration into existing systems**
- **Trusted** and **versatile**
- **Option: false finger detection** with optronic sensor

Convenient software

- **MorphoAccess® Enrollment & Management System (MEMS)**: complete application for centralized management (enrollment, terminals management, log editing, verification station)
- **Morpho Integrator's Kit (MIK)**: enables integrators to interface rapidly their own proprietary Windows® based applications to the OMA 500 Series.
- **Software Development Kit (SDK)**: can be proposed to VARs who want to develop and embed their own applications in the terminal.

Technical specifications

MorphoAccess® unit

- Integrated MorphoSmart™ sensor 23x23mm, 500 dpi
- LCD graphical display 128x64 pixels
- Keypad with 12 Keys + 4 programmable function keys
- Buzzer and LED
- Dual-core ARM 9 microprocessors with multi-thread processing capability

Multiple interfaces

- Communication port for identifier management: customizable Wiegand IN & OUT, RS 485, RS 422, Clock & Data IN & OUT, Ethernet (10/100 Base T), **Wi-Fi** in option

Large database

- From 3,000 to 50,000 people, two fingerprints each, split up into five databases of 10,000 individuals each (option, capacity submitted to MA-Xtended license)

High security level

- SSL on TCP/IP network
- Secure screws, antitheft and anti-tamper switches

Environmental conditions

- Operating temperature: -10° to +50° C
- Relative humidity: from 10 to 80% without condensation
- Waterproof, anti-dust protection: IP 65 rated

Certifications

- PIV IQS* by the FBI, FIPS 201
- CE and FCC compliant

Voltage supply

- 9V to 16V (350mA typical @ 12V) or **Power Over Ethernet (POE)**

Physical characteristics

- Dimensions: LxHxD: 218x289x99mm
- Weight: 2kg

	OMA 520 D	OMA 521 D
Contactless reader/encoder	MIFARE® 1K & 4K, DESFire® 2K, 4K, 8K	
Database size	3K or 50K with MA-Xtended license	
Fake Finger Detection	No	Yes
Multi-factor authentication	BIO, Card, Card+BIO, PIN+BIO, Card+PIN, Card+PIN+BIO, Card+PIN+BIOPIN**	

* PIV-IQS Personal Identity Verification - Image Quality Specifications

** BIOPIN alternate password solution instead of fingerprints

Morpho

Phone: +33 (0)1 58 11 73 42 - Fax: 33 (0)1 58 11 89 93 - www.morpho.com - www.biometric-terminals.com
Registered Office : Le Ponant de Paris - 27, rue Leblanc - F-75512 PARIS CEDEX 15 - FRANCE
Société anonyme au capital de 159.876.075 euros - 440 305 282 R.C.S. PARIS